EP5502

Impactful High-Definition Digital Poster

VERSATILE VIDEO 55" DIGITAL SIGN BOARD

Overview

ViewSonic's new ePoster products make it easy to replace those old backlit printed signs with new impactful video messaging on high definition digital posters. These sleek new displays feature versatile input connections for easy content uploading or adding your favorite media player. Information is disseminated through the ePoster's video connectors via or media player or USB thumb drive. ViewSonic's new ePoster products are available in various sizes and slim profiles fit in beautifully with their limited footprint. Great for announcing special promotions, computergenerated information or communicating multimedia with photos, audio, signage, and video.

Features

- 55"" Full HD 1920x1080 display resolution
- 450 nits of brightness with 5,000:1 contrast ratio
- Sleek tempered glass faceplate
- Versatile video inputs (HDMI, VGA, YPbPr, USB)
- Easy loading of content through USB thumb drive
- Internal VESA mounting and power supply for adding media players
- Compatible with the ViewSonic NMP-570 (W) media player (Optional)
  Includes Signage Manager Express software
- Audio 2x5w
- Applications:
  - Retail Advertising
  - Transportation
  - Hospitality
  - Education

1 – Security Latch/Handle
2 – RJ45 Ethernet LAN port
(extension to optional media player)
3 – 3x USB 2.0 Ports
4 – 2GB CF Card Storage
5 – HDMI Port
6 – VGA Input
7 – YPbPr/Composite Video/Audio
8 – PC Audio
9 – USB Port
10 – AC Power Male Port
11 – AC Power Female Port
12 – Power On/Off

Technical Specifications

COMPATIBILITY	Photo Formats	JPEG
	Video Formats	MPEG 1/2/3, H.264, Xvid 1.00–AVI, MP4
	Audio Formats	WMA, MP3, M4A (AA CC)
DIMENSIONS	Physical With Stand	32.68" x 78.7" x 17.72" (830mm x 2000mm x 450mm)
REGULATIONS		FCC, ICES 003, CE
PACKAGE CONTENTS		ePoster, power cord, remote control with batteries, key, Quick Start Guide, User Manual and Software on CD
AUDIO	Speaker	5W (x2)
CONNECTOR	Network	Ethernet RJ-45 (10/100M)
	USB	2.0 (x1)
	Card Reader	2GB Compact Flash
POWER	Consumption	Max 450W
	Save Mode (W)	Off < 1W
DISPLAY	Contrast Ratio	5000:1 (typ)
	Brightness	450 cd/m2 (typ)
	Type	Diagonal: 55" (139.7 cm)

For more product information, visit us at **www.viewsoniceurope.com**

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.

ViewSonic® See the difference™

	Resolution	1920x1080 dots
	Color Depth	Over 16.7M color (depending on video card used)
	Response Time	6.0ms (typ gray-to-gray)
	Viewing Angles	Up and down 178°, left and right 178° (typ) @ CR>10
WEIGHT	Gross	297.6 lbs. (135 kg)
	Net	264.5 lbs. (120 kg)
OPERATING CONDITIONS	Humidity	20–90% (non-condensing)
	Temperature	32–104° F (0–50° C)
CONNECTORS		HDMI, VGA, YPbPr, USB, A/V, RJ45 Pigtail
STORAGE ENVIRONMENT	Humidity	10–90% (non-condensing)
	Temperature	-4–140° F (-20–40° C)
CONTENT MANAGEMENT	Operating System	MS Windows
	Software	Signage Manager Express
MTBF		50,000 hrs.

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.